

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application.

**Listing of Claims:**

1. (Currently Amended) A centerwinder for receiving and winding a constantly fed web material comprising:

at least two winding shafts, said at least two winding shafts are positioned approximately parallel to one another and independently rotate in the same direction in a stationary structure; ~~and~~

a lay-on arm assembly, said web material passes through said lay-on arm assembly and is wound on one of said winding shafts to a predetermined quantity, said lay-on arm assembly:

(i) cuts said web material upon obtaining said predetermined quantity of said web material on said winding shaft; and

(ii) transfers said cut constant feed of said web material to another of said winding shafts;

a positioning apparatus and a control means for said lay-on arm assembly, said positioning apparatus and said control means maintain a constant pressure of a lay-on roll of said lay-on arm assembly against a roll of said web material as said web material is wound onto said winding shaft; and

**Appl. No. 10/816,426**  
**Amendment dated July 29, 2005**  
**Reply to Office Action of Feb. 1, 2005**

a spherical support for each of said winding shafts, each said winding shaft pivots on said spherical support.

2-3 (Canceled)

4. (Currently Amended) The centerwinder of claim 2 1 wherein said positioning apparatus and said control means for said lay-on arm assembly moves said lay-on arm assembly from said winding shaft having said predetermined quantity of said web material to an empty winding shaft.

5-7 (Canceled)

8. (Currently Amended) A centerwinder for receiving and winding a constantly fed web material comprising:

a first winding shaft and a second winding shaft, said first winding shaft and said second winding shaft are positioned approximately parallel to one another and independently rotate in the same direction in a stationary structure;

a lay-on arm assembly, said web material passes through said lay-on arm assembly and is wound into a roll on said first winding shaft to a predetermined quantity, said lay-on arm assembly:

**Appl. No. 10/816,426**  
**Amendment dated July 29, 2005**  
**Reply to Office Action of Feb. 1, 2005**

(i) maintains a constant pressure of a lay-on roll against said roll of said web material as said web material is wound onto said winding shaft;

(ii) cuts said web material upon obtaining said predetermined quantity of said web material on said first winding shaft; and

(iii) transfers said cut constant feed of said web material to said second winding shaft;

a positioning apparatus and a control means for a lay-on roll assembly of said lay-on arm assembly, said positioning apparatus and said control means operates a knife and a transfer roll mechanism to cut said web material and to transfer a leading edge of said cut web material to said second winding shaft; and

two spherical supports, each of said two spherical supports affixed to one end of each of said first winding shaft and said second winding shaft, said first winding shaft and said second winding shaft both independently pivot on their respective one of said spherical supports.

9-10 (Canceled)

11. (Currently Amended) The centerwinder of claim ~~10~~ 8 further comprising:

a shaft puller, said shaft puller independently removes said first winding shaft and said second winding shaft from said roll of said web material and reinserts said removed first winding shaft and second winding shaft into an empty core for receiving web material.

**Appl. No. 10/816,426**  
**Amendment dated July 29, 2005**  
**Reply to Office Action of Feb. 1, 2005**

12-14 (Canceled)

15. (New) A centerwinder for receiving and winding a constantly fed web material comprising:

at least two winding shafts, said at least two winding shafts are positioned approximately parallel to one another and independently rotate in the same direction in a stationary structure;

a lay-on arm assembly, said web material passes through said lay-on arm assembly and is wound on one of said winding shafts to a predetermined quantity, said lay-on arm assembly:

(i) cuts said web material upon obtaining said predetermined quantity of said web material on said winding shaft; and

(ii) transfers said cut constant feed of said web material to another of said winding shafts;

a positioning apparatus and a control means for said lay-on arm assembly, said positioning apparatus and said control means maintain a constant pressure of a lay-on roll of said lay-on arm assembly against a roll of said web material as said web material is wound onto said winding shaft; and

a shaft puller, said shaft puller removes each of said winding shafts from said roll of said web material and inserts each of said removed winding shafts into an empty core for receiving web material.

**Appl. No. 10/816,426**  
**Amendment dated July 29, 2005**  
**Reply to Office Action of Feb. 1, 2005**

16. (New) The centerwinder of claim 15 wherein said positioning apparatus and said control means for said lay-on arm assembly moves said lay-on arm assembly from said winding shaft having said predetermined quantity of said web material to an empty winding shaft.